

L.N. 412 of 2002

**THE METROLOGY ACT
 ACT NO. XXV OF 2002**

Tyre Pressure Gauges Regulations, 2002

IN exercise of the powers conferred by article 19 of the Metrology Act, the Malta Standards Authority has made the following regulations:—

1. (1) The title of these regulations is the Tyre Pressure Gauges Regulations, 2002.

(2) These regulations shall come into force on such date or dates as the Authority may by notice in the Gazette appoint and different dates may be so appointed for different purposes and different provisions of these regulations. Citation and commencement.

2. In these regulations, unless the context otherwise requires, all the definitions of the Malta Standards Authority Act shall apply. Definitions.

3. These regulations shall apply to pressure gauges intended to measure the inflation pressure of motor-vehicle tyres, as defined in Section I of the Annex. Scope.

4. (1) The tyre-inflation equipment eligible for EEC marks and signs is described in the Annex. It shall be subject to EEC pattern approval and EEC initial verification under the conditions laid down in the Annex hereto.

(2) No person may refuse, prohibit or restrict the placing on the market and entry into service of tyre-inflation equipment on grounds relating to its metrological qualities if it bears the EEC pattern approval or the EEC initial verification mark

ANNEX

1. Scope

For the purposes of this Annex, 'tyre pressure gauges' are instruments not fitted with pre-setting devices used in fixed or mobile installation for inflating motor-vehicle tyres in which mechanical measuring system transmits the elastic deformation of a sensing element to an indicating device.

They also include the pressure difference (P_c) between the air in the tyre and the atmosphere.

They also include all those parts between the tyre and the sensing element.

2. Metrological requirements

2.1. *Maximum permissible errors*

The maximum permissible positive or negative errors given in the table hereunder are defined as absolute values according to the measured pressure:

Measured pressure	Maximum permissible errors
not exceeding 4 bar	0.08 bar
above 4 bar but not exceeding 10 bar	0.16 bar
above 10 bar	0.25 bar

The maximum permissible errors must not be exceeded in the range 15 to 25°C. This range is hereafter termed the 'temperature reference range'.

2.2. *Variation due to temperature*

The variation in pressure-gauge readings at temperatures lying outside the reference range but between -10°C and + 40°C is given in the table hereunder:

Measured pressure	Maximum permissible variation
not exceeding 4 bar	0.1% of 4 bar degree Celsius
above 4 bar not exceeding 10 bar	0.05% of 10 bar degree Celsius
above 10 bar	0.05% of the upper scale limit per degree Celsius

2.3. *Hysteresis error*

Hysteresis error in pressure must not exceed the absolute value of the maximum permissible error, at any temperature within the temperature reference range. This temperature must remain constant throughout the test.

For given pressure, the value measured for increasing pressure must not exceed the value measured for decreasing pressures.

2.4. *Return of the instrument's index to a predetermined mark*

At atmospheric pressure, the pressure gauge index must stop opposite the zero mark or opposite a predetermined mark clearly differentiated from the scale intervals, within the limits of the maximum permissible error. A pressure gauge may possess a stop at a distance corresponding to at least twice the value of the maximum permissible error below zero or below the predetermined mark.

3. **Technical requirements**

3.1. *Construction*

Pressure gauges must be robustly and carefully constructed to ensure that they retain their metrological characteristics.

3.2. *Indicating device*

3.2.1. Indicating devices are graduated in bar, the value of the scale intervals being fixed at 0.1 bar.

3.2.2. In the measurement range, the indicating device must make it possible to read off, directly and accurately, the value of the pressure measured. To this end, the thickness of the part of the index which covers the scale marks must not be greater than the thickness of the scale marks themselves. The index must be capable of covering approximately half the length of the shortest scale marks. The maximum distance between the index and the plane of the scale marks must not be greater than the length of a scale division and must in no case exceed 2 mm or $0.02 L + 1$ mm in the case of circular-dial indicating devices (L being the distance between the axis of rotation of the pointer and its extremity).

3.2.3. The scale intervals must be equal over the entire scale. The scale spacings, which must not be less than 1.25mm, must be either virtually equal or show only slight variations. Variation of scale spacing is permitted if the difference between two consecutive scale spacings does not exceed 20% of the largest value and if the difference between the smallest and the largest scale spacings does not exceed 50% of the largest value.

Every fifth mark must be distinguished from the others by its greater length; every fifth or tenth mark must be numbered. The thickness of the marks must be virtually constant and must not exceed one-fifth (1/5) of the scale spacing.

4. Inscriptions and marks

4.1. *Inscriptions*

4.1.1. Compulsory inscriptions

Pressure gauges must bear the following inscriptions:

(a) on the dial:

- the symbol for the quantity measured P_c ,
- the symbol for the units of measurements, bar,
- where necessary, a sign indicating the working position of the instrument;

(b) on the dial, data plate or on the instrument itself:

- manufacturer's identification particulars,
- identification particulars of the instrument,
- the EEC pattern approval mark.

These inscriptions must be directly visible, easily legible and indelible under normal conditions of use and must not impede reading of the instrument indication.

4.1.2. Optional inscriptions

Pressure gauges may also carry additional inscriptions authorized by the competent national authority, provided that they do not impede reading of the instrument indication.

4.2. *Verification and sealing marks*

A suitable place must be provided for affixing the EEC initial verification marks.

The pressure gauges must be capable of being sealed in such a way as to render it impossible to alter characteristics of the instrument.

5. EEC Pattern Approval

EEC pattern approval of pressure gauges must be carried out in accordance with the provisions of the Measuring Instruments Regulations

At least two pressure gauges must be submitted for examination when application is made for pattern approval. The competent national authority may ask for additional pressure gauges to be supplied, depending on the progress of the tests.

5.1. *Verification of compliance with technical and metrological requirements*

Pressure gauges submitted for EEC pattern approval shall undergo an examination to ensure that they comply with the technical requirements set out in sections 2, 3 and 4.

The examination comprises the following tests, which are performed by means of reference pressure gauges whose errors must not exceed one-quarter (1/4) of the maximum permissible errors for the pressure gauges tested.

5.1.1. Determination of instrument error

Pressure gauge readings are checked at not fewer than five points (including a point near the upper and lower limits of the measuring range) distributed evenly over the scale.

5.1.2. Determination of hysteresis error

This test is to be performed only on instruments which, in normal use, are designed to measure decreasing pressures.

The test consists in taking readings at not fewer than five points on the pressure gauge (including a point near the upper and lower limits of the measuring gauge) distributed evenly over the scale at increasing and decreasing pressure values.

In the case of decreasing values, the readings must be taken after the pressure gauge has been kept at a pressure equal to the upper limit of the measuring range for 20 minutes.

5.1.3. Examination of the stability of the properties of pressure gauges

The tests consist in subjecting pressure gauges to:

- (a) a pressure exceeding the upper limit of the measuring range by 25% for 15 minutes;
- (b) 1 000 pulses produced by a pressure varying from 0 to 90-95% of the upper limit of the measuring range;

- (c) 10 000 cycles of the pressure varying slowly from approximately 20% to approximately 75% of the upper limit of the measuring range at a frequency not exceeding 60 cycles per minute;
- (d) an ambient temperature of - 20°C for six hours and a temperature of + 50°C for six hours.

On completion of tests (a), (b) and (c) and after being left to stand for one hour, the pressure gauges must satisfy the requirements set out in sections 2.1, 2.3 and 2.4.

On completion of the temperature test referred to in (d), the pressure gauges must be left to stand at a temperature in the temperature reference range for six hours. After this period, the pressure gauges must satisfy the requirements set out in sections 2.1, 2.3 and 2.4.

5.1.4. Variation due to temperature

The test consists in determining the change in reading for a given pressure at temperatures of -10°C and +40°C compared with the reading in the temperature reference range.

6. **EEC Initial verification**

EEC Initial verification of pressure gauges is carried out in accordance with Measuring Instruments Regulations.

6.1. *Examination of conformity*

This examination consists in checking the conformity of the pressure gauge with the approved pattern.

6.2. *Verification tests*

These tests are performed by means of reference pressure gauges whose errors must not exceed one-quarter (1/4) of the maximum permissible errors for the pressure gauges submitted for verification.

6.2.1. Determination of errors

Pressure gauge readings are checked at not fewer than three points distributed evenly over the measuring range.

6.2.2. Determination of hysteresis

Hysteresis error must be checked only in case of pressure gauges which can measure increasing and decreasing pressure pursuant to sector 2.3.

The relevant test consists in taking readings at no fewer than three points on the pressure gauge, distributed evenly over the measuring range, for increasing and decreasing pressure values. The test must be performed under normal conditions of use.